

Build As You Go~All the Way Through

How to use this technique for adding borders and creating bed-sized quilts

Yes, it can be done easily!

Incorporating Sashing into the design element of your quilt is the first step!

Supplies Needed:

Batting Tape: 3/4" or 1" wide

For Bed quilts I prefer the 1" tape for extra strength

For wall quilts and Art quilts, 3/4" is preferred for design purposes

Tape Makers

Bias tape makers such as Clover-3/4" for the back side of the quilt and 1" for the front side.

The Ultimate Sasher Collection- Pauline's Quilters World

3/4" for the back and 1" for the front OR

1" for the back and 1 1/8" for the front

Always use the smaller sashing on the backside

Fuse your batting tape on the front side, making sure the tape is centered on the raw edges.
For best results, your sashing should be slightly wider than your batting tape.

Make your quilt in sections using the traditional BAYG method. This includes any extra quilting that you wish to do through the backside of the quilt.

To join your sections~join one section at a time.

Figure A: Fuse the batting tape to the top

Figure B: Sew the narrow sashing to the backside, covering the raw edges.

Figure C: Flip back to the front and cover the batting tape with the wider sashing. You will see that the stitches will show through on the backside, but the backside stitches will be covered by the sashing on the front.

And that's all there is to it!

Figure A



Figure B



Figure C

